

PRV

PATENT- OCH REGISTRERINGSVERKET
Patentavdelningen

Intyg Certificate

Härmed intygas att bifogade kopior överensstämmer med de handlingar som ursprungligen ingivits till Patent- och registreringsverket i nedannämnda ansökan.

This is to certify that the annexed is a true copy of the documents as originally filed with the Patent- and Registration Office in connection with the following patent application.



(71) Sökande Kemira Kemi AB, Helsingborg SE
Applicant (s)

(21) Patentansökningsnummer 0203529-3
Patent application number

(86) Ingivningsdatum 2002-11-28
Date of filing

REC'D 10 DEC 2003

WIPO PCT

Stockholm, 2003-11-25

För Patent- och registreringsverket
For the Patent- and Registration Office

Lisa Junegren

Lisa Junegren

Avgift
Fee

PRIORITY DOCUMENT
SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH
RULE 17.1(a) OR (b)

BEST AVAILABLE COPY

+46 40 260516

AWAPATENT AB

Kontor/Handläggare
Malmö/Frida Björk

KEMIRA KEMI AB

Ansökningsnr

Vår referens

SE-2020947t. Patent-01

1

7002 -11

Huvudfaxer

A METHOD FOR SUPPLYING OXYGEN TO A WATER PURIFICATION
PROCESS

Technical field of the invention

The present invention relates to a method for supplying oxygen to a water purification process and to the use of at least one copolymer of dimethylsiloxane, ethylene oxide and propylene oxide, as an oxygen carrier in water purification.

Background Art

The processing and disposal of wastewater treatment sludge are increasingly important topics of environmental, economical and technological concern. Recently, the waste volumes produced have increased dramatically as a result of increases in the organic loading of wastewater and environmental regulations that require a higher degree of wastewater treatment. After sewage treatment at wastewater plants there is still over 1 million ton sludge produced each year in Sweden. By tradition, this sludge has been spread out on fields as fertilizer, or it has been deposited or combusted. However, many problems have arisen. In 1999 Lantbrukarnas Riksförbund, the farmer's national union in Sweden, warned their members from using sludge as fertilizer as they suspected the sludge to contain hazardous substances. Disposal by land filling is also becoming increasingly expensive. The growing and closing of landfills, public concerns over ground-water contamination and safety problems associated with methane production as a result of biological activity in landfills further expand the problem. Public concern over possible hazardous products through combustion processes such as dioxins and possible heavy metal contamination from the resulting ash is also problematic. Therefore a new waste tax was introduced in January 2002 to encourage researchers to find a better

2002 -11- 2 8

Huvudfaxen Kassan

2

5 solution. By year 2005, the situation becomes even more critical as by then it will be completely illegal to deposit organic material as sludge. Therefore, the problem with the great amount of sludge mass is urgent today.

10 Certain wastewater treatment methods comprise biological techniques, such as aerobic treatment, anaerobic treatment, and other anoxic processes (denitrification, sulphate reduction). The biological techniques clearly have the greatest potential for treating wastewater. Biological processes can be used to remove and/or recover biodegradable organic compounds, nitrogen, phosphorus and sulphuric compounds, pathogenic organisms and various heavy metals.

15 Biological processes are used extensively in the treatment of domestic and industrial wastewater. The quality of the effluent water depends on effective removal of the pollutants by metabolic activity of the aerobic microorganisms. The activity depends on the growth rate which is regulated by the dissolved oxygen and medium composition. Aerobic conditions are favouring oxidation of substances responsible for the unpleasant odour of fermented sludge.

25 Oxygen solubility has always been an important issue in many aerobic fermentation processes, because oxygen unlike other nutrients is sparingly soluble in aqueous media. The mass transfer rate of oxygen from oxygen rich phase to media is often a rate limiting factor in the processes. Therefore oxygen has to be continuously supplied to media to meet the oxygen demand required for actively respiring cells to do the metabolism which will not be effected by the lack of oxygen. Shortage of dissolved oxygen is hampering the biological digestion of sludge and oxidation reaction e.g. denitrification and detoxication of wastewater. Bioremediation of hazardous toxicants such as dioxins and pesticides is oxygen dependant.

Today the lack of oxygen in the biological purification steps is partially solved by supplying oxygen by pumping to these biological steps. This requires a high energy supply which is expensive.

5 However, since there still remains a considerable amount of sludge, which must be deposited and discarded, new means for supplying oxygen to the biological steps are required, so that a more effective digestion is accomplished.

10 In WO86/03773 there is described a process for increasing the solubility of gases in an aqueous medium and an emulsion for carrying out said process. Said emulsion comprises a copolymer of a silicone and a hydrophilic compound.

15 Due to the restricted laws regarding disposal of organic material as sludge in the coming years there are urgent needs to develop new means to digest sludge more efficiently. The present invention provides a solution to the above mentioned problem.

20 Summary of the Invention

The present invention relates, in one aspect, to a method for supplying oxygen to a water purification process, said method comprising:

- 25 a) providing a carrier of at least one copolymer of dimethylsiloxane, ethylene oxide and propylene oxide;
b) adding said carrier to the water purifying process; and
c) contacting said carrier with an oxygen containing gas; steps b) and c) being carried out in optional order.

30 The invention relates, in another aspect, to the use of at least one copolymer of dimethylsiloxane, ethylene oxide and propylene oxide, as an oxygen carrier in water purification.

Detailed description of embodiments of the invention

35 In an embodiment of the invention said copolymer is added as an emulsion, or as a copolymer immobilized on and/or in a support. An emulsion may be used for example

for increasing the oxygen content of contaminated waste water, thereby increasing the digestion of heavier material such as sludge. The copolymer may be emulsified in any solvent known to a person skilled in the art, an
5 example being water or any oil. A support immobilized with said copolymer may be used for increasing the oxygen content for bioremediation of the waste.

The carrier of at least one copolymer of dimethyl-
siloxane, ethylene oxide and propylene oxide added to the
10 water purifying process may be combined with other known means for increasing the oxygen content in water. A certain water purifying process is not limited to a certain copolymer, but a combination of different
15 copolymers of dimethylsiloxane, ethylene oxide and propylene oxide may be added together or separately to the water purification process.

In a further embodiment said copolymer immobilized on a support further includes immobilized microorganisms thereon. Said support may be selected from the group
20 consisting of organic supports, such as alginate, collagen, glycans, and so on, and non-organic supports, such as ceramics, polystyrene in the form of hollow fiber membranes, and the surfaces of beads. Any support known
25 within the art may be used in connection with the invention and will be apparent to a person skilled in the art. By co-immobilizing the copolymer with microorganisms and oxidative enzymes participating in aerobic processes, the contact of the oxygen carrying copolymer and the
30 microorganisms and oxidative enzymes is facilitated, thereby getting easy access to the required oxygen. The oxidation process is accelerated.

In a yet further embodiment said oxygen containing gas is added to the process either continuously or batch-
wise. By continuously adding oxygen to the process the
35 copolymer can continue to function as an oxygen carrier over time. As the oxygen is consumed by the aerobic processes further oxygen can be continued to be supplied

+46 40 260516

Ink. t. Patent- och reg.verket

2002-11-28

5

Huvudfaxen Kessen

to the copolymer. The supplied oxygen gets into contact with the copolymer, being depleted of oxygen, and the copolymer takes up oxygen and continues to act as an oxygen carrier.

5 In the context of the present invention the wording "oxygen containing gas" refers to any kind of gas containing oxygen, examples being air or pure oxygen gas.

10 In an embodiment of the invention said copolymer is added to the aerobic steps of the water purifying process. In the present context the wording "aerobic step(s)" is meant to comprise any step(s) of a water purification process in a water purification plant requiring oxygen for the digestion of sludge or any contaminants in the waste water.

15 In another embodiment of the invention said at least one copolymer comprises 10-40 % by weight of dimethylsiloxane, 20-60% by weight of ethylene oxide, and 10-60 % by weight of propylene oxide.

20 In a yet further embodiment said copolymer comprises 15-35% by weight of dimethylsiloxane, 25-45% by weight of ethylene oxide and 20-50% by weight of propylene oxide. Non-limiting examples of copolymers which present satisfactory results in connection with the present invention are a copolymer comprising 18% by weight
25 dimethylsiloxane, 35% by weight ethylene oxide and 46% by weight propylene oxide and a copolymer comprising 33% by weight dimethylsiloxane, 44% by weight ethylene oxide and 23% by weight propylene oxide.

30 The copolymers are used for supplying the desirable oxygen amount to the microorganisms requiring oxygen for their metabolism, i.e. digestion of sludge. Further, the copolymers are used for transporting other gases, e.g. carbon dioxide, produced in the digestion of the sludge. The copolymers may be added to the aerobic steps of a
35 water purification process in any form, examples being as an emulsion or immobilized on a support. Any form which suits the copolymer may naturally be used in the scope of

the present invention. The amount required is generally low and the copolymer is biodegradable. Thus, a further advantage of the invention is that the copolymer degrades after some time and it is not necessary to remove the remainders from the process. Thus, it is only required to add further copolymer to the water purifying process if further purification is needed.

Both agitation and air compression, being used today for supplying oxygen, consume a considerable amount of energy. Therefore, copolymers of dimethylsiloxane, ethylene oxide and propylene oxide can serve as a cheap solution to enhance oxygen levels in aerobic steps in water purification. It is important to select a proper copolymer of dimethylsiloxane, ethylene oxide and propylene oxide, since it has been shown in the present invention that certain copolymers supply oxygen more efficiently than others.

Brief description of drawings

Figure 1. Oxidation rate of different concentrations of glucose by immobilised glucose oxidase, monitored by thermometric sensor.

Figure 2. The effect of the polydimethylsiloxane (PDMS) copolymers, with increasing concentrations of PDMS, on the enzymatic glucose oxidation. The tested samples are in table 1. In each analyzed sample glucose (2.5 mM) was present. Symbols: 1) no polymer; 2) 15% DC Q2-5247; 3) 0.5% DC1248+15% DC Q2-5247; 4) 5%DC1248 + 15% DC Q2-5247; 5) 15% DC 1598; 6) 0.5% DC1248+15% DC 1598; 7) 5%DC1248 +15% DC 1598; 8) 15%DC1248+ 0.5% PPG P2000.

Figure 3. The role the poly ethylene/propylene block in the PDMS copolymer has on the enzymatic glucose oxidation. In each analyzed sample glucose (2.5 mM) was present. Symbols: 1) no polymer; 2) 15% DC Q2-5247; 3) 15% DC Q2-5247+ 5% pluronic F 68; 4) 15% DC 1598; 5) 15% DC 1598+ 5% pluronic F 68.

Figure 4. Enzymatic glucose oxidation in the presence of polydimethylsiloxane (PDMS) copolymers and

Perfluorodecalin. Symbols: 1) no polymer ; 2) 15% perfluorodecalin +5% pluronic F 68; 3) 15% DC 1598+5% pluronic F 68; 4) 15% DC Q2-5247+5% pluronic F 68; 5) 15%DC 1248 +0.5% PPG P2000

- 5 Figure 5. Growth curve of *Bacillus thuringiensis* with and without DC Q2-5247 added into LB growth medium

Examples

MATERIAL AND METHODS

Preparation of thermistor based enzyme unit

- 10 Glucose oxidase (GO) with horseradish peroxidase (HRP) were covalently co-immobilized on amino-controlled-pore glass beads (CPG) by using glutaraldehyde chemistry. CPG was activated with 2.5% glutaraldehyde solution dissolved in phosphate buffer (0.1N, pH 7.0). To
15 350 mg of activated CPG beads were added 10 U of dialyzed glucose oxidase and peroxidase in phosphate buffer. The coupling of the enzymes was carried out overnight at 4°C under gentle shaking. Afterwards, in order to terminate all the unreacted groups on the matrix 50 mg ethanol
20 amine (pH 8.5-9.0) was added and allowed to react further for 2 h. Finally, the immobilised enzymes were washed with the (10 vol) phosphate buffer and the beads were transferred into a column (0.7 ml, 2.5 cm x 0.7 cm) and assembled into the thermometric system belonging to the
25 unit called enzyme thermistor (ET).

Assay

- The reaction velocity is determined by converting the produced heat during the enzymatic oxidation of glucose into electrical signals read as peaks. The size
30 of the integrated peak area is proportional to the concentration of the oxidized glucose. Each new measurement started with standardization of the system using glucose (0.5-3.5 mM).

Preparation of siloxanes for the enzymatic test

- 35 Preparation of the running buffer. The running buffer consists of (100mM) sodium phosphate, pH 7.0 in which (10mM) 2.4 o-dianisidine was dissolved.

Preparation of oxygen carrier emulsion with glucose. In the case when the PDMS copolymer was not water soluble a constant concentration (0.5% w/w) of polypropylene glycol P2000 (PPG P2000) or up to 5% (w/w) Pluronic F 68 (trademark for a series nonionic surface-active agents prepared by the addition of ethylene oxide to the propylene glycols) as emulsifier was used. A given concentration of a PDMS copolymer with or without emulsifier was dissolved in the running buffer and sonicated for 2 minutes in Bronson water bath (40 mHz). Freshly prepared suspension was quickly distributed in 5 ml portions into labeled test tubes pre-filled with a defined glucose concentration. Before the injection into the enzyme thermistor (ET) system each suspension was saturated with pure oxygen for 2 minutes, and (100 µl) was injected into ET which was running at constant flow rate (0.7 ml /min).

Reagents

A 25 % aqueous solution of glutaraldehyde, Glucose oxidase (GO type X-S, from *Aspergillus niger* 208 U mg⁻¹) and 2.4 o-dianisidine were purchased from Sigma Chemical CO (USA). Peroxidase (HRP) (250 U/mg) was obtained from Biozyme Laboratories. Glucose, yeast extract and bactopectone (digested casein) were obtained from Merck. (Darmstadt/Germany). Polypropylene glycol P2000 (PPG P2000) was a gift from MB-Sveda/Sweden, and Polydimethyl siloxane (PDMS) co-polymers were kindly obtained from Dow Corning (DC) USA supplied by the distributor in Belgium. Trosoperl controlled-pore glass (CPG) beads with free amino groups (particle diameter 125-140 nm, pore diameter 49.6 nm) were obtained from Schuller (Steinach, Germany). All solutions were prepared with phosphate buffer (sodium phosphate dibasic with sodium phosphate monobasic) 0.1 mol l⁻¹ at pH 7.0.

Organisms

Bacillus thuringiensis, a laboratory strain and *Streptomyces coelicolor* A3(2) were used in these studies.

The *Bacillus thuringiensis* was maintained at 4°C on LB agar slants, and the inoculum was built by transferring one loop of cells from the agar slant to 100 ml of liquid LB media (500 ml flask). The LB media consist of; yeast extract-0.5%, bactopectone-1% and NaCl-1%, pH 7.0.

5 *Streptomyces coelicolor* A3(2) was maintained at 4°C on protein fraction extract (PFE) agar plate and spores were used for preparing a PFE based liquid inoculum.

Cultivation conditions

10 The growth was carried out in the 3 L Erlenmeyer flasks filled with LB (1 litre) growth media and supplemented with 0.01-0.1% (w/w) of PDMS copolymer (DC Q2-5247) for *Bacillus* and 0.1-5% for *Streptomyces* and as control no oxygen carrier was added. Each flask was

15 closed with a tight stopper jointed to a gas filter. The gas filters were connected with a plastic tube to a sterile filter and further joined with the main air supply via an Erlenmeyer flask filled with water sacking bottle saturated under controlled flow of air. To keep

20 the cultivation bottles under controlled temperature and agitation, during the growth, they were placed in a water bath with a set temperature and agitation speed. During defined hours by using a sterile syringe up to 50 ml of cell suspension was drawn out for analysis.

25 Cell count The cell count was carried out for the bacillus cell culture. The samples were serially diluted with saline solution (0.9% NaCl). The appropriately diluted samples (0.1ml) were plated on LB agar plates and incubated at 30°C for 24h to form fully developed

30 colonies.

Pigmented Actinorhodin determination Actinorhodin production has been checked out as follows: a known volume of liquid medium with growing bacteria was mixed with 2M KOH and left for 30 min., then centrifuged (10

35 min., 20000g). The Actinorhodin content was measured in the supernatant. Absorbance at $\lambda=550$ nm was followed by a

Hitachi U-3200 UV/VIS spectrophotometer (Kieser et al., 2000).

Screening of PDMS copolymers by using glucose oxidase /peroxidase thermosensor

A few commercially available Dow Corning (DC) PDMS co-polymers (table 1) were chosen and screened for their potential to increase the oxidation rate of glucose by using a co-immobilised glucose oxidase/peroxidase where the registration of the enzymatic reaction was combined with the thermal unit known as enzyme thermistor (ET). This study has already indicated that such chemicals have a high potential for increasing oxygen solubility in water and do not kill the enzymes or microbial activity. However, guidelines regarding the proper choice of a commercial product like the size and the proportion of the inbuilt blocks, its capacity to carry oxygen from water to the enzyme or microbial system are missing. As it is shown in fig 1, the glucose concentration continues to increase 0.5-1mM, an increase of reaction rate is observed as first order kinetics (phase 1). As the substrate concentration increases from 1.5-2.0 mM, the increase in the reaction rate begins to slow down, and with a large substrate concentration from 2.5-3.5 mM, no further change in velocity is observed, phase 2 entering the zero-order kinetics. The reasons of the zero-order kinetics in the case of oxidases at this range of glucose is due to the limited concentration of dissolved oxygen.

Different PDMS copolymers (table 1) at concentration range between 0.5 to 25%(w/w) were tested with glucose in the range between 0.5-3.5 mM. The oxidation rate of glucose gets satisfactorily improved when 2.0 mM glucose is combined with 15% of each PDMS copolymer listed in table 1.

35 The individual PDMS co-polymer was suspended in water based solutions. In some experiments the PDMS copolymers were combined with polypropyleneglycol P2000 (PPG P2000) or with Pluronic F 68. The choice of these

substances was based on the structural similarity to the non PDMS block (table 1). Without glucose, PPG P2000 and Pluronic F 68 at concentration 1 and 5% (w/w) respectively, passed through glucose oxidase sensor without producing a heat signal. The PPG P2000 used at a concentration of 1% (w/w) with 1.5 mM glucose was not effective to improve glucose oxidation, while Pluronic F 68 used at a concentration of 5 % (w/w) has less capacity to improve oxygen solubility on its own. To see the role of the block ratio of PDMS on the oxidation of 2.5 mM glucose 15% (w/w) PDMS copolymers were tested (table 1). Another aspect was to see how the increased concentration of PDMS moiety either present in the copolymer structure, or added separately into the water-based solution affects the glucose oxidation rate (figure 2). The product DC 1248 that is almost a pure PDMS (table 1) was tested in combination with PPG P2000 (bar 8), DC Q2 -5247 (bar 3,4) and DC 1598 (bar 6,7) in figure 2. The almost pure PDMS marked DC 1248, added in the amount of 5% (w/w) together with 15% either DC Q2-5247 or DC 1598 shows a neglectable effect.

The effect of the non PDMS moiety in tested copolymers is shown in figure 3. It is interesting that Pluronic F 68 at 5% (w/w) used together DC 1598 (bar 4, 5) improves the oxygen carrying capacity of the DC 1598 while similar combination with DC Q2-5247 (bar 3,4) is not effective at all (figure 3). The explanation of these results is the critical role of the PDMS ratio to the EO/PO block. In spite of the fact that PDMS is the key carrier for oxygen, the EO/PO block is the limiting factor for the oxygen carrying capacity.

Effect of a PDMS copolymer on model bacteria

PDMS copolymer marked Q2-5247 was tested for its effect on multiplication of cells by *Bacillus thuringiensis* or antibiotic production by *Streptomyces coelicolor*. In case of the *Bacillus thuringiensis* strain, the optimal final concentration of the PDMS

copolymer used was 0.05%(w/w) (figure 5.) . Higher concentrations were not satisfactory, data not shown here. The model strain was chosen due to the fact that it is a representative anaerobic strain and also that this particular species is a producer of a biopesticide. In this work we have not measured the level of the biopesticide, but one could expect that its level could be also increased. In some cases the improved oxygen solubility is not expressed in the form of an increased mass but in form the of an increased level of metabolites (Ziomek et al., 1991, Elibol 2001). Similar to Elibol (2001), we tested Q2-5247 for its potential to improve the actinorhodin, an antibiotic product by *Streptomyces coelicolor*(A3). The results from the blue-pigmented antibiotic actinorhodin are shown in table 2. In this model study the optimal concentration of the used PDMS polymer, added at the beginning of the culture growth is 0.1% (w/w) .

In the microbial system described in the literature, perfluorodecalin as oxygen carrier is more often used than PDMS copolymers, in spite of the fact that it is very expensive and it has to be used in high concentrations in microbial systems to improve a biological process. Moreover, using perfluorodecalin to improve fermentation yield, high waste loads are created which might be problematic for the natural bioremediation system.

Table 1. The distribution of the main components in the polymerised blocks of the commercially available Dow Corning (DC) polydimethylsiloxanes (PDMS) which were tested with glucose oxidase is shown below.

Product name	Dimethyl siloxane (%)	E0 (%)	PO (%)	Mw	Viscosity
DC 1248	96	0	2	3100	170
DCQ2-5247	18	35	46	27900	2305

13

DCQ2-5573	19	35	46	58047	4450
DC 5604	24	50	26	6700	300
DC 1598	33	44	23	9590	548
DC 3581	95	4	1	31282	7500
DC 3580	17	1	83	5105	312

EO=ethylene oxide PO= propylene oxide

5 Table 2. The production of actinorhodin by *Streptomyces coelicolor* A3(2) on the protein fraction extract (PFE*) based growth medium without and with addition of PDMS copolymer marked DC Q2-5247 . The data are expressed in OD units measured at λ 550 nm followed in the supernatant from the growth culture.

Sampling time (h)	without PDMS (OD)	0.1% (w/w) PDMS (OD)	0.5% (w/w) PDMS (OD)
60	0,11	0,20	0,13
84	0,12	0,33	0,17
132	0,13	0,31	0,17
156	0,27	0,36	0,24

*PFE protein fraction extract

CLAIMS

1. A method for supplying oxygen to a water purification process, said method comprising:
 - 5 a) providing a carrier of at least one copolymer of dimethylsiloxane, ethylene oxide and propylene oxide;
 - b) adding said carrier to the water purifying process; and
 - 10 c) contacting said carrier with an oxygen containing gas;
 wherein steps b) and c) being carried out in optional order.
2. A method according to claim 1, wherein said copolymer is added as an emulsion, or as a copolymer
 15 immobilized on and/or in a support.
3. A method according to claim 2, wherein said support immobilized copolymer further includes immobilized microorganisms thereon.
4. A method according to claim 2 or 3, wherein said
 20 support is selected from the group consisting of organic supports and non-organic supports.
5. A method according to any one of claim 1-4, wherein said oxygen containing gas is added to the process either continuously or batch-wise.
- 25 6. A method according to any one of claims 1-5, wherein said copolymer is added to the aerobic steps of the water purifying process.
7. A method according to any one of claims 1-6, wherein said at least one copolymer comprises 10-40 % by
 30 weight of dimethylsiloxane, 20-60% by weight of ethylene oxide, and 10-60 % by weight of propylene oxide.
8. A method according to claim 7, wherein said copolymer comprises 15-35% by weight of dimethylsiloxane,
 25-45% by weight of ethylene oxide and 20-50% by weight
 35 of propylene oxide.

15

9. Use of at least one copolymer of dimethylsiloxane, ethylene oxide and propylene oxide, as an oxygen carrier in water purification.

10. Use according to claim 9, wherein said at least one copolymer comprises 10-40 % by weight of dimethylsiloxane, 20-60% by weight of ethylene oxide, and 10-60 % by weight of propylene oxide.

11. Use according to claim 10, wherein said copolymer comprises 15-35% by weight of dimethylsiloxane, 25-45% by weight of ethylene oxide and 20-50% by weight of propylene oxide.

Figure 1


ABSTRACT

The present invention relates to a method for supplying oxygen to a water purification process, said
5 method comprising providing a carrier of at least one copolymer of dimethylsiloxane, ethylene oxide and propylene oxide, adding said carrier to the water purifying process, and contacting said carrier with an oxygen containing gas. The invention further relates to
10 the use of at least one copolymer of dimethylsiloxane, ethylene oxide and propylene oxide, as an oxygen carrier in water purification.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157


1/5

Fig 1




2/5

Fig. 2



3/5

Fig. 3



+46 40 260516


Ink. t. Patent- och reg

7802 -11- 2

Huvudfaxon Ka


4/5.

Fig. 4



5/5

Fig. 5



**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER: _____**

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.